Form 3160-5 (June 1990)	DEPART	TED STATES IT OF THE INTERIOR AND MANAGEMENT	N.M (14) 311 8, 1st Ar Nim	FORM APPR 10-2834 Budget Bureau No. Expires March 3	OVED 1004-0135
Do not use this form	5. Lease Designation and NM-7714 7719	5. Lease Designation and Serial No.			
1. Type of Well Gas ⊠ Oil Weil 2. Name of Operator DEVON ENER	West Red Lake Unit 8. Well Name and No.				
 Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 2310' FNL & 990' FEL, Unit "H", Section 7-18S-27E 				9. API Well No. 30-015-10174 10. Field and Pool, or Exp Red Lake (Q-GB-SA 11. County or Parish, Sta	
CHECK AP TYPE OF SU) TO INDICATE NATURE	E OF NOTICE, RE TYPE OF ACTIC		ATA
 Notice of Intent Subsequent Report Final Abandonment Notes 	ACCEPTED FOR REC MAY 1 1 1998	Plugging Back Casing Repair Altering Casing		Change of Plans Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple con Completion or Recompletion Report	n npletion on Well

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Administrative Order WFX-726

Work began 4/20/98. TIH w/ CIBP & set @ 1200'. TIH w/ pkr & set above CIBP, tested to 1000 psi. TOH w/ pkr to 950', pumped into Premier perfs w/ 4 BPM @ 1300#. TOH w/ pkr. Squeezed Premier perfs 1044'-1064' w/ 150 sx class "C". POH w/ tbg & setting tool. Drld cmt retainer & cmt. Tested to 350# for 5 min, drld out CIBP. RU & perf'd San Andres w/ 1 SPF as follows: 1584', 1596', 1598', 1600', 1602', 1604', 1606', 1608', 1630', 1632', 1634', 1640', 1642', 1648', 1650', 1652', 1654', 1656', 1658', 1660', 1662', 1664', 1666', 1670', 1672', 1682', 1684', 1694', 1700', 1702', 1704', 1712', 1714', 1716', 1718', 1720', for a total of 36 holes. Acidized w/ 5000 gals 15% NeFe acid + 2000# rock salt. ISIP 1070#. TIH w/ pkr & 2-3/8" tbg., set pkr @ 1000'. Tested to 300 psi for 15 min. Chart attached. Began water injection 4/28/98 into San Andres perfs 1584'-1720'.

PostID-3

5-29-98

		prod 20 mm
14. I hereby certify that the foregoing is true and correct	Tonja Rutelonis	
Signed Xufflows (This space for Federal or State office use)	Title Engineering Technician	Date <u>4/30/98</u>
Approved by Conditions of approval, if any:	Title	Date
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and w	ilifiilly to make to any denotront or ananyy of the Units	d States any false florizious or fraudulent statements or representation
to any matter within its jurisdiction.	many to that to any department of agency of the office	



.

· · ·