

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*
(Other instructions on reverse side)

Form approved. *Copy 127*
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 058126

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates Federal "B" ✓

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Loce Hills ✓

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19-16S-29E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Ernest A. Hanson

3. ADDRESS OF OPERATOR
P. O. Box 1515, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

**990' FNL & 1980' FEL
Sec. 19, T. 18 S., R. 29 E.** ✓

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3571' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-18-63

Ran 8-5/8" @ 326' set in drlg. mud.

No fluid was encountered in hole until total depth was reached where 3 gals. of oil per hour was tested.

10-10-63

The 8-5/8" was pulled and 5-1/2" casing run to 2460' and cemented w/100 sacks. A 15 sack cement plug was set in mud @ 326' in the annulus between the 5-1/2" casing and 10" hole. A 5 sack cement plug was set in the annulus at the surface.

RECEIVED

DEC 24 1963

G. G. G.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry F. Schuman

TITLE

Geologist

(This space for Federal or State office use)

APPROVED BY
COMMISSIONS OR APPROVAL, IF ANY:

TITLE

DATE

12-19-63

DATE

*See Instructions on Reverse Side

APPROVED
DEC 23 1963
F. L. SEE
DISTRICT ENGINEER

RECEIVED
DEC 23 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.