'JNITED STATES DEPAR . MENT OF THE INTERIOR (Other Interior verse side)

SUBMIT II

IPLICATE* ions on re-

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT—" for such proposals.)				
OIL X GAS WELL OTHER		ais.)	7. ONIT AGREEMENT NAME	
Ernest A. Hanson			8. farm of least name Yates, Folomol "S"	
P. O. Box 1515, Roswe	ll, New Mexico		9. WELL NO.	
See also space 17 below.) At surface Sec.	early and in accordance with any State FNL & 1980' FEL 19, T-18-S, R-29-E, N.I County, New Mexico	•	10. FIELD AND POOL, OR WILDCAT LOCO HILLS 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, 35771 DF	GR, etč.)	Sec. 19 - 18S - 29E 12. COUNTY OF PARISH 13. STATE Eddy N. Mex.	
.6. Check Ap	propriate Box To Indicate Natur	re of Notice, Report, or C	e- 1-2	

NOTICE	OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Base of Salt 782' Perfs. 2378-2426' Top of Salt 370 T.D. 2461' P.B.T.D. 2460' 5-1/2" @ 2460' w/100 sx.

The captioned well was plugged and abandoned effective November 1, 1967, in the following manner:

- The hole was displaced with heavy mud.
- 2. A 20 sack cement plug was spotted across the perfs. @ 2289-2460'.
- Set one shot of nitro at 1937' and couldn't pull.
- Shot 5-1/2" casing @ 1905' & pulled.
- A 20 sx. cement plug was spotted @ 1930' and in-and-out of 5-1/2" casing.
- A 20 sx. cement plug was spotted @ 723-790' at base of salt.
- A 20 sx. cement plug was spotted @ 360-427' at top of salt.
- A 20 sx. cement plug was spotted @ 0-28' at top of hole.
- A regulation dry hole marker was erected.
- The location was cleaned-up and made ready for final inspection by 10. the U.S.G.S.

the U.S.G.S.		CEIVER	
18. I hereby certify that the foregoing is true and correct	•	JAN-21900	
SIGNED TO THE STATE OF THE STAT	TITLE _	Exploration Manuel	r DATE 12-20-67
(This space for Progral or State office use)	TITLE _	ARIC	DATE

*See Instructions on Reverse Side