

NM OF CONS. COMMISSION
Drayer DD
UNITED STATES
Artesia, NM 88210
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED BY

SEP 12 1984

Form Approved.
Budget Bureau No. 42-R1424

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Yates Drilling Company

3. ADDRESS OF OPERATOR

207 South 4th Street, Artesia, N.M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit B, 990' FNL and 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Re-entry

5. LEASE

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

D.

OFFICE UNIT AGREEMENT NAME

South Loco Hills Unit

8. FARM OR LEASE NAME

South Loco Hills Unit

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Loco Hills-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 19-18S-29E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3571' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/26/84 Cleaned out to 580'. Ran 8 jts., 8 5/8" csg. and 5' shoe joint. Cemented w/ 100 sxs. Class "C" Cement w/ 2% CaCl₂. Drilled out cement and plug to 1905' Ran 1889' 5 1/2", 14# csg, unable to get back inside old csg. Kicked 7" sleeve over old csg., got inside old csg., cleaned out to 2375'. Cemented new 5 1/2" csg. w/100 sxs. Class "C" cement.

Perforated 2375'-81' and 2414'-25', 38, .44" holes (2 SPF.)

Frac'd w/40000 gals. gelled water, 1500 gals 15% acid, 65000# 10/20 and 20/40 sand.

Set pumping equipment.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Clerk DATE

9/5/84

ACCEPTED FOR RECORD (Place for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

SEP 7 1984

Carlsbad,

NEW MEXICO

*See Instructions on Reverse Side