

(SUBMIT IN TRIPLICATE)

Land Office New MexicoLease No. NM-033775

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

R. Manning Federal "b" NCT-1
Le No. 43971Texaco Inc. P.O. Box 728
Hobbs, New Mexico January 14, 1963Well No. 2 is located 660 ft. from {N} line and 560 ft. from {E} line of sec. 27SW/4, SW/4, Sec. 27

(1/4 Sec. and Sec. No.)

18-S

(Twp.)

30-E

(Range)

NMPM

(Meridian)

North Benson Queen-(Field) GrayburgEddy

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3445 ft.

DETAILS OF WORK

State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

TD-3299'

9-5/8" O.D. Casing cemented at 522'.

Ran 3298' of 4 1/2" O.D. casing (9.5 lb. J-55) and cemented at 3299'.
Plug at 3297. Cement with 500 sx Class "A" 4% gel and 100 sx Class "A" cement. Job complete 11:30 P.M., January 10, 1963.Bailed hole dry. Tested plug from 1:00 to 1:30 P.M., January 11, 1963.
No fluid entry. Bailed hole dry. Tested ok. Job complete January 11, 1963.

understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Texaco Inc.Address P.O. Box 728Hobbs, New MexicoBy J. BlinTitle Asst. District Superintendent

