

Form 9-331a
(Feb. 1951)**APPROVED**JUL 2 1963
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBudget Bureau No. 42-R358.4.
Form Approved.Land Office ~~Artesia, N. Mex.~~Lease No. ~~LC 088~~ 719-A

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

13 June, 19 63

Well No. 1 is located 1980 ft. from N line and 1980 ft. from W line of sec. 29NE/4 SW/4
(1/4 Sec. and Sec. No.)18S
(Twp.)NM PM
(Meridian)Not designated
(Field)Eddy
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3445 ft.**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casing; indicate mudding jobs, cementing points, and all other important proposed work)

See Attached Sheet

(Report of 5-31 / 6-6 / 6-11 /)

RECEIVED

JUL 3 1963

O. C. C.
ARTESIA, OFFICE**RECEIVED**JUN 20 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Floyd W. Smith & Company, INC.Address P. O. Box 1518
Midland, TexasBy Kevin E. HaldenTitle Asst. Gen. Mgr.

03/11/2011
11:00 AM
11:00 AM

03/11/2011
11:00 AM
11:00 AM

DRILLING REPORTS U. S. A. LIGHT # 1

5/31/63 - - 546' Sd RR Anhy & Salt Ran 527.88' 24#. 10V thread 7" csg set at 529' and cemented w/125 Sx Trinity Portland cement w/10# Salt/Sx & w/2°/° HA 5 in last 50 Sx cement circ comp at 07:30, 5/31/

6/6/63 - - 3250 and & lm 265' TD Reached @ 0600 - POH Ran GR-Sonic & Laterolog - Went in hole LD DP Ran 99 jts 3150.65' 4 1/2" 9.50# J-55 csg. w/5 cent. at 3051, 3022, 2961, 2862, and 2802. Set at 3150' & Cemented w/43 Sx Trinity Portland mixed w/42 Sx Pozmix 5 / 4% Gel, tailed in with 48 Sx Portland Trinity Reg Neat cement. Pumped dn plug w/10,4# SW. Comp at 8:30 p. 6-6.

6/11/63 - - Moved in pulling unit - ran 2" tbg. to 3130'. Displaced salt water w/lease crude and spotted 250 gal 15 °/° NE acid- POH. Ran GR correlation log and perf 4 1/2" csg w/8 3/8" holes at 3039, 3038, 3035, 3034, & 2992, 2991, 2988, 2987. Broke dn formation w/lease crude and dropped 6 ball sealers and pumped in 250 gal 15 °/° NE acid. Initial break dn press 2700 - - 2400 Press after dropping balls 3500#. Fraced w/20,000 gal refined oil w/20,000 gal refined w/30,000# 20/40 & 10/20 sand. Treating press 2900# 10 min CIP 1900#. Comp. 5p 6/11 Cl. 645 OLTR.

APPROVED

JUL 2 1963

RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

RECEIVED

JUL 3 1963

D. C. C.
ARTESIA, OFFICE

RECEIVED

JUN 20 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

