

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa FeLease No. NM-0630Unit C

Cyt 57

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT (Temporary) <u>x</u>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 15, 19 63

LDY

Well No. 1 is located 990 ft. from [N] line and 2310 ft. from [W] line of sec. 26SE-NE-NW Sec. 26 18S 25E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Wildcat Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is _____ ft. 3485' GL

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth is 1722 feet in the San Andres. This well has been temporarily abandoned with the following procedure: Heavy mud from 1722 to 1150 feet, 75 sack cement plug from 1150 to 1020 feet, bridge plug of 2"x 4"x 4' lumber with wire line wickers at 720 feet, gravel from 720 to 703 feet, 20 sacks cement plug from 703 to 620 feet, heavy mud from 620 to surface. A 8 5/8" metal marker has been used to designate well site.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company MARTIN YATES, IIIAddress 309 Carper BuildingArtesia, New MexicoBy R. L. NormanTitle Geologist