

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other instruc.
verse side)ATE*
on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0630

6. IF INDIAN, ALLOTTED OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LDY

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Pines

11. SEC., T., R., M., OR BLK. AND

26-18S-25E NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Martin Yates, III

3. ADDRESS OF OPERATOR

323 Carper Building-Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

990' FNL and 2310' FWL Section 26-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3485 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 2-11-67 - Set Cardinal Select Liners at following intervals: 1570-1592½' & 1654-1688' to cover previously Sand Frac zones.
- 2-11-67 - Sand fraced down the casing using 40,000# 20-40 sand, 4052 bbls. gelled brine water, 48 bbls displacement water, 85 gal 14N surfactant and 100,000# salt used for blocking agent. Bottom of 4½" casing at 1722'.
- 2-16-67 - Retrieved Select Liner at interval 1570-1592½' - could not retrieve the liner at 1654-1688' - slipped down the hole during the frac job - fished for liner and retrieved same. Put well back on pump to test.

RECEIVED

MAR 15 1967

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

MAR 15 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

M. L. Armstrong

TITLE

Agent

DATE

3-14-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 17 1967

*See Instructions on Reverse Side