

(SUBMIT IN TRIPLICATE)

Land Office **Las Cruces**Lease No. **LC 064226**

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 25, 1964

Well No. **1** is located **2310** ft. from **[N]** line and **2310** ft. from **[E]** line of sec. **27**

24/422/4 (1/4 Sec. and Sec. No.)	T-189 (Twp.)	R-302 (Range)	S.M.P. (Meridian)
North Benson (Field)	Hddy (County or Subdivision)	New Mexico (State or Territory)	

The elevation of the derrick floor above sea level is **3486** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Featherstone Trust No. 1 CHAD-Federal:

T.D. 3420'. Ran 3420' 5-1/2" 13.50 3 rd STD Casing w/float shoe and six (6) centralizers. Halliburton Cemented w/200 sac liner 30-50 possix with 85 Gel and 140 sac liner 30-50 possix with 25 Gel followed by 600 gal acetic acid and water, circulated 20 sac.

WOC 24 hrs. Tested Casing w/600# for 30 min. Pressure held.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **OLEN F. FEATHERSTONE II TRUST**Address **236 Petroleum Bldg.****Hoswell, New Mexico**

By

Title

Geologist

