

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>MARATHON OIL CO.</u>		Lease <u>GUY W. NICKSON "A"</u>		Well # <u>I</u>	
Location of Well	Unit <u>NENE A</u>	Section <u>30</u>	Township <u>18^S</u>	Range <u>26^E</u>	County <u>EDDY</u>
Drilling Contractor	<u>GARDNER BROS. DRG. CO</u>		Type of Equipment <u>ROTARY</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11"</u>	<u>8 5/8"</u>	<u>32 #</u>	<u>NEW</u>	<u>2000'</u>	<u>CIRCULATE</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>17 #</u>	<u>NEW</u>	<u>9250'</u>	<u>600</u>
Casing Data:					
Surface <u>63</u> joints of <u>8 5/8</u> inch <u>32 #</u> Grade <u>J.S. A.P.I. New pipe</u> (Approved) (Rejected)					
Inspected by <u>LOBLEY</u> date <u>3-14-63</u>					
Cementing Program					
Size of hole <u>11</u> Size of Casing <u>8 5/8</u> Sacks cement required					
Type of Shoe used <u>GUIDE</u> Float collar used <u>W.C. FLO</u> Btm 3 jts welded <u>TAPER-LOK</u>					
TD of hole <u>2004</u> Set <u>2002</u> Feet of <u>8 5/8</u> Inch <u>32 #</u> Grade <u>J.S. A.P.I.</u>					
New used csg. @ <u>2002</u> with <u>200</u> sacks neat cement around shoe + <u>200 GEL + 1/4" FLOCEL</u>					
+ <u>200</u> sax <u>Test</u> additives <u>200 GEL + 1/4" FLOCEL</u>					
Plug down @ <u>1st stage 6:20 (PM)</u> Date <u>3-18-63</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>25</u>					
Cemented by <u>DOWELL</u> Witnessed by <u>LOBLEY</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ <u>4:10 (PM)</u> Date <u>3-20-63</u>					
Method used <u>800# pressure</u> Witnessed by <u>LOBLEY</u> <u>O.K.</u>					
Remarks: <u>2nd stage D.V. Tool at 975' with 960 lbs. Lib. wt. + 12# GEL + 1/4" FLOCEL</u> <u>and 100 lbs. neat + 200 GEL + 1/4" FLOCEL. Plug down 4:05 am 3-19-63</u> <u>450 lbs. Circulated.</u>					

600 TL 10 1/2 G. 1/4 flo.

200 reg. 200 GEL 1/4 flo.

860 LW 8 1/2 G. 1/4 flo.
1000 reg. 200 GEL 1/4 flo.

9/5 D.V.