

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

NOV 27 1978

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p><b>SUNDRY NOTICES AND REPORTS ON WELLS</b></p> <p>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p> <p>5. State Oil &amp; Gas Lease No. L-1605</p>
<p>1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- (Old well re-entered)</p> <p>2. Name of Operator McClellan Oil Corporation</p> <p>3. Address of Operator P.O. Box 848, Roswell, New Mexico 88201</p> <p>4. Location of Well UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 18-S RANGE 23-E NMPM.</p>		<p>7. Unit Agreement Name</p> <p>8. Farm or Lease Name State "AR"</p> <p>9. Well No. 1</p> <p>10. Field and Pool, or Wildcat Wildcat Wellcamp</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 4083.6 G.L.</p>		<p>12. County Eddy</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9.5" Re-entry operation was commenced 11/10/78. Cleaned out to 4610'. Ran logs 4½" casing was run 11/23/78 to 4606'. Cemented with 250 sx 50-50 posmix, 2% gel 3/10 of 1% CFR and 8 lbs. salt per sack. Casing was 9½ lb. J-55. Tested 1500 lbs. Ran temptarture survey 11/24/78. Plug back T.D. 4552'. Top of cement 3620'.

Prep to perforate and acidize.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jack J. McClellan

TITLE Operator

DATE 11/24/78

APPROVED BY W.A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE NOV 28 1978

CONDITIONS OF APPROVAL, IF ANY: