 2) By at Duat 3) RJ 4) Pr Pr 5) PC 1 hereby certision and certisio and certision and certisio and certisio and certisio	y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure cha	RIH with IH with CI cement on oing to 267 t 5 1/2" c It 5 1/2" c It attache down tubir	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed. ng. Rig do	Pull tubing and junk bas at 2714' (to 3P with dump b alated hole wi 300 psi for 15 own pulling un 71 5 Area Superin	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798'). fluid.	· · · · · · · · · · · · · · · · · · ·
 2) By at Du 3) RJ 4) Pr Pr 5) P(y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure tes OH and lay	RIH with IH with CI cement on oing to 267 t 5 1/2" c rt 5 1/2" c rt attache down tubir	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed. ng. Rig do	g and junk bas t at 2714' (to 3P with dump b 11ated hole wi 300 psi for 15 own pulling un	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798'). fluid.	-
 2) By at Du 3) RJ 4) Pr Pr 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure cha	RIH with IH with CI cement on ping to 267 t 5 1/2" c rt attache	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed.	g and junk bas t at 2714' (to 3P with dump b 1lated hole wi 300 psi for 15	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798').	
 2) By at Du 3) RJ 4) Pr Pr 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure cha	RIH with IH with CI cement on ping to 267 t 5 1/2" c rt attache	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed.	g and junk bas t at 2714' (to 3P with dump b 1lated hole wi 300 psi for 15	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798').	
 2) By at Du 3) RJ 4) Pr Pr 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure cha	RIH with IH with CI cement on ping to 267 t 5 1/2" c rt attache	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed.	g and junk bas t at 2714' (to 3P with dump b 1lated hole wi 300 psi for 15	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798').	
 2) By at Du 3) RJ 4) Pr Pr 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes ressure cha	RIH with IH with CI cement on ping to 267 t 5 1/2" c rt attache	gauge ring IBP and set top of CIE 79'. Circu casing to 3 ed.	g and junk bas t at 2714' (to 3P with dump b 1lated hole wi 300 psi for 15	ket and set op perf. at 2 bailer. POH. th inhibited minutes-OK.	798').	
 By at Du R1 R1 P1 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes	RIH with IH with CI cement on ing to 267 t 5 1/2" c	gauge ring IBP and set top of CIF 79'. Circu casing to 3	g and junk bas t at 2714' (to 3P with dump b lated hole wi	ket and set op perf. at 2 pailer. POH. th inhibited	798').	
 By at Du R1 R1 P1 	y wireline, t 2714'. R ump 35' of IH with tub ressure tes	RIH with IH with CI cement on ing to 267 t 5 1/2" c	gauge ring IBP and set top of CIF 79'. Circu casing to 3	g and junk bas t at 2714' (to 3P with dump b lated hole wi	ket and set op perf. at 2 pailer. POH. th inhibited	798').	
2) By at Du	y wireline, t 2714'. R ump 35' of	RIH with IH with CI cement on	gauge ring IBP and set top of CII	g and junk bas t at 2714' (to 3P with dump b	ket and set op perf. at 2 ailer. POH.	798').	
2) By at	y wireline, t 2714'. R	RIH with IH with CI	gauge ring IBP and set	g and junk bas t at 2714' (to	ket and set of perf. at 2	down 798').	
				-			
	TDII mulli-~			Du11 L-L-1.			
· ·		unit T-				•	
Reclass 6/10/88	sify from S B.	I-INJ to I	R-INJ (He)	ld for Remedia	1 Work) effec	ctive	
nent to this	work.) *				· · · · · · · · · · · · · · · · · · ·	evere peru	
DESCRIBE PROP proposed w	POSED OR COMPLETED O ork. If well is direct	PERATIONS (Clearly tionally drilled, give	state all pertinent d subsurface location	etails, and give pertinent d s and measured and true v	dates, including estimated ertical depths for all ma	g torm.) date of starting any rkers and some parti	
REPAIR WELL (Other)	• •	CHANGE PLANS		(NOTE : Report re	rary Abandon sults of multiple complet completion Beport and Lo	ion on Well	
BHOOT OR ACT	<u> </u>	ABANDON*		SHOOTING OR ACIDIZING			•
PRACTURE TR	EAT	MULTIPLE COMPLET	те	FRACTURE TREATMENT		IG CABING	
TEST WATER	SHUT-OFF	PULL OR ALTER CA	SING	WATER SHUT-OFF		NG WELL	-
	NOTICE OF INT		l l	,	BREQUENT REPORT OF :		
· ·	Check 4			ure of Notice, Report,		1 1 4 F 1	
			' DF		Eddy	NM	
PERMIT NO.		15. ELEVATIONS	(Show whether DF, BT,	, 03, etc.)	Sec. 29,	T185, R30	E
Unit Le	etter F, 23	10' FNL &	1650' FWL		BURYNT OR A	•	
					11. BBC., T., B., M.,		G
See also space At surface	17 below.)	cically and 10 8000	isaur with aby Sta	** *** OFFICE	10. FIELD AND POO		~
PO BOX	728, Hobbs	, NM 8824	0	C. C. D.	10		
ADDRESS OF O	PERATOR	······			9. WBLL NO.	QUEEN UT	۱
Texaco	Inc.			JUL 14'88	N. BENSON		•
WELL L	WELL JOTHER	Water I	njection W	ell	North Be	nson Queen	U
	GAB			RECEIVED	7. UNIT AGREEMEN	T NAME	
	Use "APPLI	ORAIS to drill or to CATION FOR PERM	deepen or plug back iIT—" for such propo	to a different reservoir.			
(Do not u					6. IF INDIAN, ALLO	TTEE OR TRIBE NAME	
(Do not u	SUNDRY NO	TICES AND	ANAGEMENT		LC-06840	TON AND BREAL NO.	-

1

Title 18 U.S.C. Section 1001, makes it a crime tor any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.