

c/SF

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

5. LEASE
NM 0924

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
(Trigg) Federal Sivley-Alscott

9. WELL NO.
5-30

10. FIELD OR WILDCAT NAME
Loco Hills-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit L, Sec. 30-T18S-R29E

12. COUNTY OR PARISH | 13. STATE
Eddy | NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3-2-2-36

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other P&A

2. NAME OF OPERATOR
Yates Drilling Co.

3. ADDRESS OF OPERATOR
207 S. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL & 1913 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

NOV 28 1983
O.C.D.
ARTESIA, OFFICE

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>

(other) Replug well. NMOCD Order No. R-7012

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Replugged well as follows: Cleaned out w/7-7/8" bit. Found top of old 8-5/8" casing at 1694'. Cleaned out to 2072'. Set 250 sx Class "C" cement plug at 2065'. Tagged plug at 1468'. Set 75 sx Class "C" cement w/2% CaCl plug at 860'. Tagged plug at 700'. Set 75 sx Class "C" cement w/2% CaCl at 450'. Tagged plug at 386'. Ran additional 50 sx Class "C" cement. Tagged plug at 350'. Set 15 sx Class "C" cement plug at surface. Installed dry hole marker.

Work started September 29, 1982. Completed work October 5, 1982.
Witnessed by Mr. Weaver, NMOCD, Artesia.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED L. Anita Goodell TITLE Engineering Secty DATE 10-18-82

APPROVED (This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:
NOV 23 1983