

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer 8D

Artesia, NM 88210

5. LEASE

NM 0925

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
(Trigg) Federal Sivley-Wright

9. WELL NO.
2-29

10. FIELD OR WILDCAT NAME
Loco Hills-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit 3, Sec. 29-T18S-R29E

12. COUNTY OR PARISH 13. STATE
Eddy NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ P&A

2. NAME OF OPERATOR
Yates Drilling Co. Agent for John H Trigg

3. ADDRESS OF OPERATOR
207 S. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
660 FNL & 1980 FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐ Replug Well

RECEIVED

SEP 13 1982

O. C. D.
ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

SEP 10 1982

U.S. GEOLOGICAL SURVEY
ROSEMONT, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

NMOCD Order No. R-7012 requires well to be replugged before commencement of injection of water in Phase I injection wells for South Loco Hills (Grayburg) Unit. TD 9262'. 35 sx plug at 8581-8681', 35 sx plug at 6524-6624', 35 sx plug at 4981-5081', 35 sx plug at 2803-2903', 35 sx plug at 1956-2056', 35 sx plug at 919-1019', 10 sx plug at surface. 8-5/8" at 955' w/500 sx. Re-enter, drill out existing plugs above Grayburg and Loco Hills. Set 50 sx plug over Loco Hills and Grayburg 100 sx plug (50' in & 50' out) at 8-5/8" casing shoe, 10 sx at surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James A. Johnston TITLE Engineering Secty DATE 9-7-82

(This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 10 1982

FOR

JAMES A. JOHNSTON

DIRECTOR, NEW MEXICO

*See Instructions on Reverse Side