Re-plug well

Form Approved.

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

other

gas

well

FRACTURE TREAT

SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE **CHANGE ZONES** 

well

	Budget Bureau No. 42-R1424
5.	LEASE
	NM-27280
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
7.	UNIT AGREEMENT NAME
	• 4
8.	FARM OR LEASE NAME
	Light "A"
9.	WELL NO.
1	1-A
10.	FIELD OR WILDCAT NAME
	•
11.	SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sac	29. T-18-S. R-30-E
12.	COUNTY OR PARISH 13. STATE
	Eddy   New Mexico
14.	API NO.
15.	ELEVATIONS (SHOW DF, KDB, AND WD)

JUL 24 198 2. NAME OF OPERATOR Texaco Inc. Wolfson 3. ADDRESS OF OPERATOR P.O. Box 728, Hobbs, NM 88240 ARTESIA, OFFICE 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF

JUL 21 1980

(NOTE: Report results of multiple completion or zone change of FATHLESON AL SURVEY ARTESIA, NEW MEXICO

Set @

ABANDON\*
(other) Texaco Inc. re-entered & re-plugged subject P&A well formerly operated by Wolfson Oil Co., in compliance w/NMOCD letter of 4-30-79.

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
- 1. Rigged up. Remove Dry Hole Marker. Install BOP.
- 2. Set 7" RBP @ 400'. Spot 324' sand on plug. Cement 7" csg annulus w/1150 sx Class "C" cement containing 2% CaCl. Follow w/100 sx Class "C" cement containing 2% CaCl. WOC. DOC. Pull RBP.
- 3. Clean to 1396'. Log well. No water movement below 1000'. Confirmed findings w/2nd log. Clean out to 1419'.
- 4. Spot 50 sx. cement plug from 1419' 1240'.5. Spot 50 sx. cement plug from 1240' 1195'.
- 6. Spot 300 sx. cement plug from 1195' 495'.

Subsurface Safety Valve: Manu. and Type \_\_\_

- 7. Spot 113 sx. cement plug from 495' surface.
- 8. Set Dry Hole Marker. Clean up. Re-plugging operations complete, 6-27-80.

18. I hereby certify that the foregoing is true and correct	
SIGNED ASST. DIST. SUPT. DATE _	7-18-80
(This space for Federal or State office use)	
APPROVED BY SELD PLANE W. CHESTER ACTING DISTRICT ENGINEER CONDITIONS OF APPROVAL IF ANY:	JUL 2 3 1980