

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Petr. Corp.</u>		Lease <u>Marathon State A.M.</u>		Well # <u>1</u>	
Location of Well	Unit <u>P</u>	Section <u>16</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>B.L. McFarland</u>			Type of Equipment <u>Rotary</u>		
APPROVED CASING PROGRAM 9100 menow approved 4-28-64					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11"</u>	<u>8 5/8</u>		<u>New</u>	<u>1300</u>	<u>Circ.</u>
<u>7 7/8</u>	<u>4 1/2"</u>		<u>New</u>	<u>9200</u>	<u>500</u>
Casing Data:					
Surface <u>45</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>used J-55 S.M. Spring</u>					
<u>HPI? rusty heat</u> (Approved) (Rejected) <u>no deep pits</u>					
Inspected by <u>Gressett</u> date <u>5-6-64</u>					
Cementing Program					
Size of hole <u>11</u> Size of Casing <u>8 5/8</u> Sacks cement required					
Type of Shoe used <u>Guide</u> Float collar used <u>no</u> Btm 3 jts welded <u>three jts</u>					
TD of hole <u>1267</u> Set <u>1267</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>1 above</u>					
New-used csg. @ <u>1267</u> with <u>100</u> sacks neat cement around shoe					
+ <u>200</u> sax <u>Incor + 2% gel</u> additives <u>2700 cc last 100</u>					
Plug down @ <u>2:00</u> (AM) (PM) Date <u>5-6-64</u>					
Cement circulated <u>720</u> No. of Sacks					
Cemented by <u>R. J. ...</u> (Signature) Witnessed by <u>Gressett</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ <u>6:30</u> (AM) (PM) Date <u>5-7-64</u>					
Method Used <u>1500</u> Witnessed by <u>Lucker (Castlemann)</u>					
Checked for shut off @ <u>1:30</u> (AM) (PM) Date <u>5-8-64</u>					
Method used <u>600</u> Witnessed by <u>Gressett</u>					
Remarks: <u>2 1/2" to 3" B.M. 100 sacks @ 12:15 PM 5-7-64 2100 cc</u>					
<u>logs stop 2 3/4" 2 1/2" finished filling to top w/ 1 1/2 yds reagent</u>					