

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

OCT 16 1968

O. C. C.
ARTESIA, OFFICE

Form C-105
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER-		6. Indicate Type of Lease State ☐ Fee ☐
2. Name of Operator Yates Petroleum Corporation /		5. Write Oil & Gas Lease No. 1-8100
3. Address of Operator 207 South 4th Street - Artesia, New Mexico 88210		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>P</u> , <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.		8. Farm or Lease Name Artesia Street
13. Elevation (Show whether D _P , RT, GR, etc.) 3370 KB		9. Well No. 1
		10. Field and Pool, or Atoka-P...
		11. County Lddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☒	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDON ☐

17. Describe Proposed or Completed Operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of completion work) SEE RULE 1103.

It is the intention of Yates Petroleum Corporation to Plug and Abandon this well in the following manner. (1) Pull tubing and packer. (2) Pull tubing open ended to 8800'. (3) Load casing with 9w mud. (4) Spot 35 (35 sx) cement plug from 8800' back to 8350' to shut off Morrow perfor. (5) Spot 450' (35 sx) plug from 5800' back to 5350' to shut off Tola perfor. (6) Free point and cut off 4 1/2" casing at approx. 4100'. (7) Spot 35 sx plug at top of 4 1/2" sub at approx 4100'. (8) Spot 35 sx plug at 2200'. (9) Spot 35 sx plug at 1260' in and out of 8-5/8" surface casing. (10) Spot 35 sx plug at 680' inside 8-5/8" casing (11) Erect and cement surface marker (12) Clean location for NMCCC inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Benjamin H. ... TITLE Engineer DATE 10-16-68

APPROVED BY W. A. Gressitt TITLE DRILLING INSPECTOR DATE OCT 16 1968

CONDITIONS OF APPROVAL, IF ANY: