

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

EX-107
SUBMIT IN TRIP. (TE)
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-029415-B

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR WILLIAM A. & EDWARD R. HUDSON	7. UNIT AGREEMENT NAME FEB 26 1982
3. ADDRESS OF OPERATOR Box #198, Artesia, New Mexico 88210	8. FARM OR LEASE NAME Puckett "B" C. C. D.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1295' from south and 1295' from west lines of Section 24-17S-31E.	9. WELL NO. 23 ARTESIA, OFFICE
14. PERMIT NO.	10. FIELD AND POOL, OR WILDCAT Maljamar
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 24-17S-31E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

On December 7, 1981, pumped 20 bbls. water with 15 mc. tracer material down bradenhead (between 5½" and 8-5/8" casing strings). This was followed by 69 bbls. water. Ran tracer logs which indicated water flow zone from 668 to 688'. On December 8, 1981, pumped 600 sacks class "C" cement with 10# salt/sx. + 3% CaCl down bradenhead. Pumped at 550 psi. at 3 BPM. Previously packer was set in 5½" casing at 2100' with 1,000 psi. on casing. Ran temperature survey, but lost fluid in tubing and survey was unsuccessful. Water flow is shut-off.

RECEIVED
JAN 15 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Consulting Engineer

DATE Jan. 14, 1982

(This space for Federal or State Office Use)

ACCEPTED FOR RECORD
PETER W. CHESTER

APPROVED BY
CONDITIONS OF

TITLE

DATE

FEB 25 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.