

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Messano Co.</i>		Lease <i>Revised</i>		Well # <i>1</i>	
Location of Well	Unit @ <i>9965-19800</i>	Section <i>36</i>	Township <i>18</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>rotary</i>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>12 1/4</i>	<i>9 3/8</i>	<i>36"</i>	<i>13</i>	<i>1300</i>	<i>500 cur</i>
<i>7 7/8</i>	<i>4 1/2</i>	<i>11.6</i>		<i>9400</i>	<i>300</i>

*9400 menow  
Approved 4-23-65*

Casing Data:

Surface *44* joints of *7 7/8* inch *36* # Grade *H-S*

(Approved) (~~Rejected~~)

Inspected by *B. L. Smith* date *5-2-65*

Cementing Program

Size of hole *12 1/4* Size of Casing *9 3/8* Sacks cement required \_\_\_\_\_

Type of Shoe used *side* Float collar used \_\_\_\_\_ Btm 3 jts welded *4*

TD of hole *1300* Set \_\_\_\_\_ Feet of *7 7/8* Inch *36* # Grade *H*

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe

+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ *11 45* (AM) (PM) Date \_\_\_\_\_

Cement circulated \_\_\_\_\_ No. of Sacks \_\_\_\_\_

Cemented by \_\_\_\_\_ Witnessed by \_\_\_\_\_

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: *TD 9325 P+A 6-9-65 @ 11:10 PM.*

*The following plugs were used: 25 sax C 9316-9221, 26 sax 9004-8905*

*30 sax 7794-7698, 33 sax 4444-4341, 26 sax 1365-1264, 29 sax 690-590*