

## NEW MEXICO OIL CONSERVATION COMMISSION

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|                                                            |          |                                                |  |
|------------------------------------------------------------|----------|------------------------------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |          | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |          | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |          | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       | <b>X</b> |                                                |  |

Jan. 6, 1952

Date

Roswell, New Mexico

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Malco Refineries, Inc.

Company or Operator

State A

Lease

Well No. 1

in the

NM, NM

of Sec. 2

T.

18 S

R.

27 E

N. M. P. M.,

Empire

Pool

Eddy

County.

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on Verbal, 19.

and approval of the proposed plan was (was not) obtained (Cross out incorrect words) Verbal

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was permanently plugged with cement as given below in regard to open hole below 7" casing @ 3700' to 8725' Total Depth and is plugged with cement up into the 7" casing. The well is temporarily abandoned with a flat plug screwed in the top of the 7" casing 3' above ground level. This well was plugged as follows with last plug in place waiting on cement @ 3:15 PM January 1, 1952. All cement slurries 15 to 16 #/gal. with 10 #/gal. drilling mud in the hole.

Plug #1 (To cover gas zone DST #6)

19 sax regular cement calculated to fill 6 1/8" hole 8168-8270.

Plug #2 (Water Zone)

44 sax regular cement calculated to fill 6 1/4" hole 4483-4720.

Plug #3 (Water zone)

8 sax regular cement calculated to fill 6 1/4" hole 4297-4340.

Plug #4 (Water zone) (Also bottom of 7" 17 1/2" casing.) 29 sax regular cement (Cont. below)

Witnessed by J. R. McKim

Name

Malco Refineries, Inc. Production Supt.

Company

Title

APPROVED:

OIL CONSERVATION COMMISSION

*[Signature]*

Name

OIL AND GAS INSPECTOR

Title

Date

19.

I hereby swear or affirm that the information given above is true and correct.

Name

J. R. McKim

Position

Production Superintendent

Representing

Malco Refineries, Inc.

Company or Operator

Address

Box 660, Roswell, New Mexico

(Cont. from above Plug #4) calculated to fill 6 1/4" hole below 3700' and 7" 17 1/2" casing above 3700', 3664-3820.

