

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

NOV 17 1978

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

O. C. C.

ARTESIA, OFFICE

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation ✓	5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 15 TOWNSHIP 18S RANGE 26E NMPM.	8. Farm or Lease Name Martin
15. Elevation (Show whether DF, RT, GR, etc.) 3333 GR	9. Well No. 1 3
	10. Field and Pool, or Wildcat Atoka S. A.
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:	
REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

After caliperizing well, it was decided not to run a liner. Hole was plugged back to 1570' and squeezed w/150 sacks of Class C cement. WOC 72 hours, drilled cement and cleaned hole to 1800'. Pay zone 1630-1650' was treated thru straddle packers with 2500 gallons NEA and well put to pumping in October, 1977. We have not been able to restore oil production. The well is now proposed for plugging and abandonment. Will set a cement retainer at about 1200' and squeeze open hole with 75 sacks of Class C, displace hole with mud and spot 20 sacks plug at 550', 10' plug at surface with marker.

\* 25

\* 10 sacks

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. Melford TITLE Engineer DATE 11-16-78

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 21 1978

CONDITIONS OF APPROVAL, IF ANY:

\* as noted above

Notify N.M.O.C.C. in sufficient time to witness

Plugging