

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 54184

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dunn B

9. WELL NO.

31

10. FIELD AND POOL, OR WILDCAT

Artesia (O,GBR, SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 11-18-28

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED BY

DEC -3 1986

O. C. D.
ARTESIA, OFFICE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

800 Central, Odessa, Texas 79761

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

B-660 FNL & 1980 FEL, Sec 11, T-18S, R-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3646 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DEPCO, Inc. plans to plug this well in the following manner: Workover pit will be required for plugging operations. Set CIBP @ 2525 w/35' cmt on top, perf @ 725' & sqz w/150 sx cmt, leaving cmt in csg. Set 10 sx plug @ surface w/dry hole marker. Mud laden fluid will be placed between all plugs.

Note: Top of perfs @ 2568'.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Denney R. L. Denney

TITLE Chief Prod Clerk

DATE 11-21-86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side