

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Martin Gato 3</u>		Lease <u>Atoka State</u>		Well # <u>2</u>	
Location of Well	Unit <u>1650 sec 5</u>	Section <u>16</u>	Township <u>18</u>	Range <u>26</u>	County
Drilling Contractor	<u>Pennsylvania Drilling Co.</u>		Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u> first half of may 1700 SA Approved 4-25-66					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>6 3/4</u>	<u>4 1/2</u>	<u>9.5</u>		<u>1170</u>	<u>Circ.</u>
Casing Data:					
Surface <u>38</u> joints of <u>4 1/2</u> inch <u>9.5</u> # Grade <u>J-S H&D C 7 1/2</u> new (Approved) (Rejected)					
Inspected by <u>G. J. Smith</u> date <u>6-29-66</u> 3.30 PM & 150					
Cementing Program					
Size of hole <u>6 3/4</u> Size of Casing <u>4 1/2</u> Sacks cement required <u>as above</u>					
Type of Shoe used <u>Float</u> Float collar used <u>10</u> Btm 3 jts welded					
TD of hole <u>1270'</u> Set <u>1270'</u> Feet of <u> </u> Inch <u> </u> # Grade <u> </u>					
New-used csg. @ <u>1256</u> with <u>40</u> sacks neat cement around shoe <u>incor</u> + <u>325</u> sax <u>incor</u> additives <u>2 1/2</u> gal					
Plug down @ <u>3:08</u> (AM) (PM) Date <u>7-7-66</u>					
Cement circulated <u>yes</u> No. of Sacks <u>incor 40 SX</u>					
Cemented by <u>Denton</u> Witnessed by <u>R. J. Smith</u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u>60'-80'</u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u>3:30</u> (AM) (PM) Date <u>7-7-66</u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>Very slight lost circulation 691'</u>					