

UNITED STATES N. M. O. C. G. COPY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	RECEIVED	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Hanagan Petroleum Corporation	AUG 18 1966	8. FARM OR LEASE NAME Sunshine
3. ADDRESS OF OPERATOR P.O. Box 1737, Roswell, New Mexico	U.S.G. ARTESIA, OFFICE	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 330' FEL		10. FIELD AND POOL, OR WILDCAT North Benson
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3436 GR	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA 31-185-90E
		12. COUNTY OR PARISH Eddy
		13. STATE N.Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Completed Producer

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/8/66 Reached total depth 3044; ran Lane Wells GR-Densilog.
Ran 98 jts. 4 1/2" - 9.6# - J-55 csg., set @ 3040', cemented
w/237 sxs Incor neat (Denton Oil Well Cementing Co.).
From PBTD 3040, tested csg. 30" @ 4000#, no drop. Cement
set 22 hrs. Perforated Lane Wells 1 shot per interval
(9 holes) 2686, 88, 2702, 04, 21, 42 (Penrose sd.) &
2995-97, 3001 (U. Grayburg), spotted 500 gals. 7 1/2% NE
acid. Sand/oil frac. (w/10% crude) 28,000 gal. plus
55,000# sand, 830 bbls. load to recover (Dowell). Pm. broke
3800#, Av. Treat. Press. 3500#, Av. Inj. Rate 19.2 BPH
8/13/66 Completed IPF 54 BOPD/24/64" ck.; no water. GOR 625:1.
TP 175#, CP 50#, Guty 36"

18. I hereby certify that the foregoing is true and correct

SIGNED

Hugh E. Hanagan

TITLE

Vice President

DATE

8/15/66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

AUG 16 1966

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local, Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for special instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local, Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well was conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 O-659224

947-4-515