

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator			Lease			Well #		
Location of Well	Unit	Section	Township	Range	County			
Drilling Contractor				Type of Equipment				
<u>APPROVED CASING PROGRAM</u>								
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement			
6 7/8		15		1250				
Casing Data:								
Surface <u>3</u> joints of <u>4 1/2</u> inch <u>9.5</u> # Grade <u>J-5 API C70</u> new								
(Approved) (Rejected)								
Inspected by <u>L. J. J. J.</u> date <u>7-26-66</u>								
Cementing Program								
Size of hole <u>6 7/8</u> Size of Casing <u>4 1/2</u> Sacks cement required								
Type of Shoe used <u>---</u> Float collar used <u>---</u> Btm 3 jts welded <u>---</u>								
TD of hole <u>1264</u> Set <u>1265</u> Feet of <u>4 1/2</u> inch <u>9.5</u> # Grade <u>J-5 API</u>								
New-used csg. @ <u>1265</u> with <u>50</u> sacks neat cement around shoe								
+ <u>3.25</u> sax <u>Linear</u> additives								
Plug down @ <u>2:50</u> (AM) (PM) Date <u>7-27-66</u>								
Cement circulated <u>yes</u> No. of Sacks <u>approx. 100</u>								
Cemented by <u>Center</u> Witnessed by <u>L. J. J. J.</u>								
Temp. Survey ran @ <u>---</u> (AM) (PM) Date <u>---</u> top cement @ <u>---</u>								
Casing test @ <u>1260</u> (AM) (PM) Date <u>8-12-66</u>								
Method Used <u>Pressure</u> Witnessed by <u>---</u>								
Checked for shut off @ <u>7:10</u> (AM) (PM) Date <u>8-12-66</u>								
Method used <u>Pressure</u> Witnessed by <u>G. P. J. J.</u>								
Remarks:								