

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	
2. Name of Operator Yates Petroleum Corporation ✓	
3. Address of Operator 309 Carper Building, Artesia, New Mexico 88210	
4. Location of Well UNIT LETTER <u>J</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3455 GR	

7. Unit Agreement Name
8. Farm or Lease Name Gerard "AW"
9. Well No. 2
10. Field and Pool, or Wildcat Penasco Draw SA 2/20
12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:	
REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1708.

11-12-66 - Spudded 11" hole at 10 AM 11-12-66.
11-15-66 - Ran 1055' of 8-5/8" 24# J-55 CF&I casing with 1 centralizer and float shoe set at 1065' KBE. Cemented with 350 sx 2% gel and 100 sx neat 2% CaCl Incor cement. Total of 450 sx. Cement circulated to surface. Cement dropped back down the hole a little and 3 yards of Ready-Mix was used to fill the hole to the surface. Plug down at 3:00 AM 11-16-66. WOC 18 hours. Drilled plug and tested casing with 600# pressure. Tested OK.

RECEIVED

NOV 22 1966

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Richard C. Norman TITLE Geologist DATE 11-22-66

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE NOV 23 1966

CONDITIONS OF APPROVAL, IF ANY: