

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instructi
verse side)CATE
on re-Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
NM 060843

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

"AY" Federal "AY"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Penasco Draw S.A. Yeso

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

25-185-25E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

309 Carper Building - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310 FNL, 1980 FWL Sec. 25-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3461 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1025 KB

TD 1050'. Ran 1035' 8-5/8" 24# J-55 csg, float shoe on bottom and 2-centralizer cemented with 175 sx of Incor, 2% CaCl, 2188# Gilsonite mixed 12.5#/sx, 44# flocele mixed 1/4#/sx, 50sx Neat Class C cement, 2% CaCl, 185 sx Class C cement 2% CaCl. Total sx 410, set at 1035'. Plug down 11-29-66.

Ran temperature survey found top of cement 601'. Ran 3/4" Kobe tubing down hole between casing and annulus to 245' from surface. Cemented with 50 sx cmt., 2% CaCl. Ran temperature survey - no fill-up. Ran 3/4" tbg. in annulus to 204', cmtd with 50 sx cmt 4% CaCl. Ran temp. survey top of cmt 125' from surface. Ran 3/4" tbg. top of cmt 135' from surface, cmtd with 50 sx cmt 4% CaCl. Ran 3/4" tbg top at 45' from surface, cmtd with 35 sx cmt 4% CaCl and filled to surface. Completed 11:40 AM 12-1-66. WOC 45 hrs. Pressure tested casing with 600# pressure for 30 minutes. Held OK.

RECEIVED

DEC 12 1966

G. G. G.
ARTESIA, OFFICERECEIVED
DEC 6 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard C. Norman

TITLE

Geologist

DATE

12-6-66

(This space for Federal or State office use)

APPROVED BY
COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
DEC 8 1966R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side