

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	2
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-4-65

Location
CORRECTED REPORT

5A. Indicate Type of Lease	
STATE <input type="checkbox"/>	FEE <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		8. Farm or Lease Name Martin	
2. Name of Operator Yates Petroleum Corporation		9. Well No. 4	
3. Address of Operator 309 Carper Building, Artesia, New Mexico 88210		10. Field and Pool, or Wildcat Atoka San Andres	
4. Location of Well UNIT LETTER 0 LOCATED 500 FEET FROM THE South LINE AND 2070 FEET FROM THE East LINE OF SEC. 15 T. 18S R. 12E NMPM		12. County Eddy	
19. Proposed Depth Approx 2300		19A. Formation San Andres	20. Rotary or C.T. Rotary
21. Elevations (Show whether DF, RT, etc.) 3336' GL	21A. Kind & Status Plug. Bond Blanket Bond	21B. Drilling Contractor Donnelly Drlg. Co.	22. Approx. Date Work will start 12-13-66

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11"	8-5/8"	24#	Approx 1150'	Approx 300	circulate to surface
7-7/8"	5-1/2"	14#	Approx 2300'	100	

If necessitated by lost circulation, a JV tool will be set on the 8-5/8" casing in the Grayburg in order to circulate the cement to the surface.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED

EXPIRES 3-8-67

RECEIVED

DEC 9 1966

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Richard C. Norman Title Geologist Date 12-8-66

(This space for State Use)

APPROVED BY A. G. Gressett TITLE OIL AND GAS INSPECTOR DATE DEC 9 1966

CONDITIONS OF APPROVAL, IF ANY.

Cement must be circulated to surface behind 8 5/8" casing

Cement behind the 5 1/2" cas. must come up at least 50' inside the 8 5/8"