

Well File

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

12-1-66

Operator <i>Yates P.T. Corp</i>		Lease <i>Martin</i>		Well # <i>4</i>	
Location of Well	Unit <i>0</i>	Section <i>15</i>	Township <i>18</i>	Range <i>26</i>	County <i>Edley</i>
Drilling Contractor <i>Donnelly</i>	Type of Equipment <i>Rotary</i>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>11</i>	<i>8 7/8</i>	<i>24 #</i>		<i>1150</i>	<i>300 circ</i>
<i>7 7/8</i>	<i>5 1/2</i>	<i>14 #</i>		<i>2300</i>	<i>100</i>

Casing Data:

Surface _____ joints of *8 7/8* inch *24* # Grade *J 5*
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *11* Size of Casing _____ Sacks cement required _____

Type of Shoe used *Float* Float collar used _____ Btm 3 jts welded *Thread lock*

TD of hole *1155* Set *1154* Feet of *8 7/8* inch *24* # Grade *J 5*

New *505X* csg. @ *ID* with *100* sacks neat cement around shoe + 2% CaCl
+ *350* sax *Class C* additives *2% gel 2% CaCl*

Plug down @ *11:18* (AM) (PM) Date *12-14-66*

Cement circulated *No* No. of Sacks _____

Cemented by *Denton* Witnessed by *P.T. Hunt*

Temp. Survey ran @ *7:30* (AM) (PM) Date *12-14-66* top cement @ *225*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ *9:00* (AM) (PM) Date *12-15-66*

Method used *Pressure* Witnessed by *PLS*

Remarks: *2nd Stage Found cement at 265'-270' with 1" tbg.*

Cement with 1505X Class C 49% CaCl 9:45 PM 12-14-66. Good circulation,

no returns. 12-15-66 12:45 AM found top of mud cement "clay"

at 30 ft, forced down to 60' Cement with Class C 505X 4% CaCl. Circulated

centralizer 1st 2nd jT above shoe cement colored water, no cement. Decided to fill up with