

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy <u>532</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>656</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers <u>1014</u>	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>1600</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>1965</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>2348</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzite _____
T. <del>*****</del> <u>2512</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abc _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. <u>Bowers 1394</u>	T. Chinle _____	T. _____
T. Penn. _____	T. <u>Penrose 1758</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. <u>Loco Hills 2050</u>	T. Penn. "A" _____	T. _____
	<u>Metex 2160</u>		

### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	64	64	Caliche, RB, sd, gravel				
64	535	471	RB, sd. strks, some Anhy				
535	548	13	Anhy				
548	580	32	Anhy, RB strks				
580	960	380	Dolo, and Rd sd strks.				
960	1280	320	Anhy, dolo				
1280	1390	110	Anhy, dolo				
1390	1440	50	Sd, dolo, some Anhy				
1440	1530	90	Dolo, Anhy				
1530	1550	20	Dolo, sd				
1550	1600	50	Dolo and some Anhy				
1600	1640	40	Sd. (Queen)				
1640	1750	110	Dolo, some Anhy				
1750	1780	30	Sd, dolo				
1780	1960	180	Dolo and sd strks				
1960	2050	90	Dolo				
2050	2070	20	Gy sd				
2070	2160	90	Dolo				
2160	2220	60	Dolo w/ sd. strks				
2220	2290	70	Dolo				
2290	2310	20	Dolo, some Rd. sd				
2310	2520	210	Dolo				
2520	2550	30	Dolo and some Gy sd.				
2550	2778	228	Dolo				

RECEIVED

JAN 26 1967

D. C. C.  
ACTING OFFICE