

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Wilkinson "AZ"
3. Address of Operator 309 Carper Building-Artesia, New Mexico 88210		9. Well No. 1
4. Location of Well UNIT LETTER N 2310 FEET FROM THE West 990 PENASCO Draw S.A. Yeso THE South LINE, SECTION 25 TOWNSHIP 18S RANGE 25E NMPM.		10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3462' GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐PULL OR ALTER CASING ☐PLUG AND ABANDON ☐CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒COMMENCE DRILLING OPNS. ☒CASING TEST AND CEMENT JOB ☒OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 13-3/8" hole at 3:00 P.M. 5-19-67 and drilled to 500', reduced hole to 12-1/4" and drilled to 1040'. Ran 1040' of 9-5/8" 32.30# H-40 casing, 1 float shoe and cemented with 645 sx of cement and 17 1/2 yards of Ready-Mix. 2 baskets at 741' and 430'. Cemented 1st stage with 320 sx of Halco light cement 2 1/2% CaCl, 12 1/2# Gilsonite, 1/4# flocele and 50 sx of Incor Neat 2 1/2% CaCl. Plug down at 5:00 P.M. 5-21-67. WOC and ran temperature survey. Found top of cement 400' from surface. Ran 3/4" Kobe tubing and spotted 275 sx of Class "C" 4% CaCl cement. Found top of cement 157' from surface. Filled to surface with 17 1/2 yards of Ready-Mix. Nippled up and pressure tested with 500# pressure. Tested OK. Resumed drilling.

RECEIVED

MAY 29 1967

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

Agent

DATE

5-26-67

APPROVED BY

TITLE

OIL AND GAS INSPECTOR

DATE

JUN 1 1967

CONDITIONS OF APPROVAL, IF ANY: