

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER 100

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Vates Pet Corp</u>		Lease <u>Mobil/B B</u>		Well # <u>1</u>	
Location of Well	Unit <u>0</u>	Section <u>24</u>	Township <u>18</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Donnelly</u>		Type of Equipment <u>Rotary</u>			

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>13 3/4</u>	<u>9 5/8</u>	<u>32.3 H</u>		<u>1000</u>	<u>grc</u>
<u>8 3/4</u>	<u>7</u>	<u>17 H</u>		<u>150?</u>	

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
 (Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 13 3/4 to 501 Size of Casing 9 5/8 Sacks cement required _____

Type of Shoe used float Float collar used _____ Btm 3 jts welded thread lck

TD of hole 1130 Set _____ Feet of 9 5/8 inch 32.3 # Grade H E

New-used csg. @ TD with 50 sacks neat cement around shoe

+ 325 sax Halliburton light additives 12 1/2 # g. per sack 1/4 # flocc per sack

Plug down @ 10130 (AM) (PM) Date 4-6-67

Cement circulated No No. of Sacks _____

Cemented by Halliburton Witnessed by _____

Temp. Survey ran @ 7:30 (AM) (PM) Date 4-6-67 top cement @ 420

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Baskets 897 & 509, SFA water 930-970, last circ

24

Time	aby depth	Sacks	Type	% Ca C	fill Cotton Seed Shells	feet of fill
10:30 PM	450	50	C	4	75 #	25'
6:17						
11:30 AM	425	50	C	4	75 #	5'
5:15 PM	420	190	C	4	1 bag	tabing ported 400' 150'
9:10 AM	360	160	C	4	1 bag	55'
3:10 PM	274	150	C	4	1 bag	70'
5:45 PM	220	150	C	4	1 bag	0
8:55	220	50	C	4	1 bag	0
8:57						
11:30 PM	210	100	C	4	2 bags	0
8-6-67 1:45	145	50	C	8	1 bag	0

Fluid level 100 feet, It was determined to fill hole from surface with ready mix