

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN PLICATE*
(Other instns on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 026874 (F)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL
WELL ☒

GAS
WELL ☐

OTHER

Drilling

2. NAME OF OPERATOR

Humble Oil & Refining Company

3. ADDRESS OF OPERATOR

Box 1600, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980 FNL & 660 FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Welch Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

S-6, T-18-S, R-27-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

To be supplied later

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

NOTE: Verbal approval to alter casing program received from USGS representative,
Mr. Jim Knauf, on 5-31-67.

Drilled to 3140' TD and ran & set 4 1/2" casing @ 3139' and cemented w/180 sax Incor
cement. Temperature survey indicates top of cement @ 1215'. PBD 3102'. W.O.C.
36 hrs.

Released rig and MIRU pulling unit. Perf. 4 1/2" casing @ 2938-44-49-59-64-68-86-89-92'
w/one shot. Acidized perfs. w/1000 gal. 15% NE regular acid. Max. 900 psi,
AIR .9 BPM, ISIP 500 psi. Began swab testing well.

RECEIVED

JUN 12 1967

RECEIVED
JUN - 7 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
6-6-67

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

JUN 12 1967