

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TR. CATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028772 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

DEPCO, INC.

3. ADDRESS OF OPERATOR

Suite 204, First National Bank, Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit Letter D 990 FNL and 330 FWL, Section 7, T.18S.-R29E.  
NMPH

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dunn A

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Artesia

11. SEC., T., R., M., OR BLK. AND

Sec. 7, T.18S., R.29E.  
NMPH

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3630 Gr

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-21-67 - Cored from 2585' to 2630', recovered 43'. Cored from 2630' to 2663', recovered 29'. T.D. 2723 K.B.

6-22-67 - Ran Gamma Ray, Density Logs.

6-27-67 - Ran 2719', 4 1/2" O.D. casing 8 jts (273') J-55, 9.5# and 77 jts. (2446') J-55, 11.6#. Cemented with 330 sx. Incor cement with 4% gel, 5/10 of 1% CFR2, 8# salt per sx. Pump plug down with 100 gal Acetic Acid and water at 1:15 P.M.

RECEIVED

RECEIVED  
JUN 28 1967  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Leon Standa*

TITLE

Engineering Assistant

DATE

June 28, 1967

(This space for Federal or State office use)

APPROVED BY

COMPLETION OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED  
JUN 29 1967  
R. L. BEEKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.