

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
		5. State Oil & Gas Lease No.
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Nix Curtis "BH"
3. Address of Operator 207 So. 4th St.-Artesia, New Mexico 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM.		10. Field and Pool, or Wildcat Penasco Draw S.A.Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3447' GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <u>7" Casing</u> <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3400' PBTD 3353'

7-22-67 - Ran 3386' of 7" OD 8R thd. 23# & 20# casing (371' of 20# J-55, 130' of 23# N-80 and 2885' of 23# J-55) set at 3386'. 1 Float disc, 1 guide shoe and 11 centralizers from 1025-3353'. Cemented with 500 sx of Class "C" cement mixed with 2% gel, 1/4# flocele, 1/2% CFR-2 and 8# salt per sack.

Ran temperature survey and found top of cement at 280'

RECEIVED

JUL 23 1967

O. P. G.
LAND OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>M. L. Armstrong</u>	TITLE <u>Agent</u>	DATE <u>7-27-67</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>LAND AND GAS INSPECTOR</u>	DATE <u>JUL 31 1967</u>

CONDITIONS OF APPROVAL, IF ANY: