

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy		T. Canyon	
T. Salt		T. Strawn	
B. Salt		T. Atoka	
T. Yates		T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen		T. Silurian	
T. Grayburg		T. Montoya	
T. San Andres	1095	T. Simpson	
	2385	T. McKee	
T. Glorieta		T. Ellenburger	
T. Paddock		T. Gr. Wash	
T. Blinebry		T. Granite	
T. Tubb	3038	T. Delaware Sand	
T. Drinkard		T. Bone Springs	
T. Abo	4963	T. Bend	8538
T. Wolfcamp	5850		
T. Penn.		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo		T. Penn. "B"	
T. Kirtland-Fruitland		T. Penn. "C"	
T. Pictured Cliffs		T. Penn. "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Qtzte	
T. Base Greenhorn		T. Granite	
T. Dakota		T.	
T. Morrison		T.	
T. Todilto		T.	
T. Entrada		T.	
T. Wingate		T.	
T. Chintle		T.	
T. Permian		T.	
T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....	2458	to.....	2637	No. 4, from.....	to.....
No. 2, from.....		to.....		No. 5, from.....	to.....
No. 3, from.....		to.....		No. 6, from.....	to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....		to.....	feet.
No. 2, from.....		to.....	feet.
No. 3, from.....		to.....	feet.
No. 4, from.....		to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1195	1195	Sand and shale				
1195	1700	505	Anhydrite, shale & Dolo				
1700	2385	685	Dolomite & Anhydrite				
2385	3036	651	Sand, anhy and shale				
3036	4963	1927	Anhy, shale & Dolo				
4963	5850	887	Shale and Dolo				
5850	6850	1000	Shale and Lime				
6850	8500	1650	Shale				
8500	9185	685	Lime, Sand and Shale				