

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN THE CATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

L.C. 029388 (d)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "A"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Mesquite Strawn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T-18-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE
N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Pennzoil United, Inc. ✓

3. ADDRESS OF OPERATOR

P. O. Drawer 1828 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surfaceUnit D - 660 FNL & FWL of Section 3, T-18-S, R-31-E
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3751' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.)*

Production on this well has declined to an uneconomical status. Plan
to plug and abandon as follows:

Spot 40 sk plug over present perforations 11,001'-11,004' inside 5 1/2"
casing set @ 12,016'. Cut 5 1/2" casing @ free point (estimated @ 7350').
Spot 25 sk plug on top of 5 1/2" stub.
Spot 25 sk plug @ 5970-6070' (Top Glorieta)
Spot 25 sk plug @ 4700-4800' (Base of 9 5/8" casing)
Cut 9 5/8" casing @ free point (estimated @ 2600')
Spot 40 sk plug @ top of 9 5/8" stub
Spot 40 sk plug @ 1960-2060' (Salt)
Spot 40 sk plug @ 736' (Base 13 3/8" casing)
Spot 10 sk plug @ surface & install marker

Mud laden fluid will be placed between all plugs.

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Petroleum Engineer

DATE

1-18-72

(This space for Federal or State office use)

APPROVED BY
CONDITIONAL APPROVAL IF ANY:

TITLE

DATE

APPROVED
JAN 20 1972
R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
JAN 19 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO