

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instructive
reverse side)DATE*
on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029388 (d)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "A"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Mesquite Strawn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T-18-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Pennzoil United, Inc.

SEP 21 1972

3. ADDRESS OF OPERATOR

P. O. Drawer 1828 - Midland, Texas - 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State Requirements.
See also space 17 below.)
At surfaceUnit D, - 660 FNL & 660 FWL of Section 3, T-18-S,
R-31-E, Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3751' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

2-14-72 Load hole w/9.5# mud laden fluid.
2-15-72 Spot 40 sk. plug fr. 10,700-11,038' & pull tubing.
2-16-72 Ran free point & shot 5 1/2" casing @ 4998'. - Pulled 4998' of 5 1/2" casing.
2-17-72 Load hole w/9.5# mud laden fluid & spot 25 sk. cement plug @ 4948' to 5048'.
(Top of 5 1/2" stub).
2-18-72 Spot 50 sk. cement plug fr. 4750-4850' (Base of 9 5/8" casing)
2-19-72 Lay down part of tubing string, load hole w/9.5# mud laden fluid.
2-21-72 Remove 8 5/8" well head. Ran free point on 8 5/8", cut 8 5/8" @ 2155' & pull
58 jts. of 8 5/8".
2-22-72 Finish pulling 8 5/8" casing. Spot 40 sk. cement fr. 2105-2205' (Top 8 5/8" stub)
Spot 40 sk. cement plug fr. 2010-2110' (Base of Salt)
Spot 40 sk. cement plug fr. 686- 786' (Base of 13 3/8" casing)
Spot 10 sk. cement plug @ surface. - Installed 4" x 4' (above G.L.) marker w/
following information.

Pennzoil United, Inc. - Federal "A" No. 1
660 FNL & 660 FWL of Sec. 3, T-18-S, R-31-E
Eddy County, New Mexico

Clear & level location

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Petroleum Engineer

DATE 3-1-72

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

SEP 21 1972
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side