

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

RECEIVED  
NEW MEXICO OIL CONSERVATION COMMISSION  
MAR 11 1968  
M. O. O.  
ADVISORY OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG 2000
7. Unit Agreement Name -----
8. Farm or Lease Name Anderson State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-
2. Name of Operator Marathon Oil Company ✓
3. Address of Operator P. O. Box 220, Hobbs, New Mexico
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>18S</u> RANGE <u>24E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3682.6 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Cement Surface Casing</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 16" hole February 15, 1968. Reached TD with 16" hole at 152' on 2-20-68. Ran 5 jts. 13-3/8" casing, Effective Length, 148.72', Overall Length 149.62'. Set from 3.00' above ground level to 146.85' below ground level. Last setting depth includes Baker guide shoe 1.13'. Cemented by Halliburton with 300 sacks of Class A, with 2% calcium chloride and 1/4# Flocele per sack. Pumping pressure 50#, Final 100#. Cement circulated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. A. Hiller Jr.</u>	TITLE <u>Area Supt.</u>	DATE <u>3-18-68</u>
APPROVED BY <u>W. A. Sussert</u>	TITLE <u>-----</u>	DATE <u>MAR 21 1968</u>
CONDITIONS OF APPROVAL, IF ANY:		