

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION  
JUN 28 1968

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator John A. Yates		8. Farm or Lease Name Ferguson
3. Address of Operator 207 So. 4th Street- Artesia, New Mexico 88210		9. Well No. 1
4. Location of Well UNIT LETTER L 940 FEET FROM THE West LINE AND 1674 FEET FROM THE South lot 3 7 TOWNSHIP 18S RANGE 26E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3429 GR		12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Re-Perforating & Sand Frac

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3300' PBTD 2708'

- 6-21-68 - Drilled out cement to 2100'. Pressured up to 1600#. Held OK.
- 6-22-68 - Drilled out cement to 2241'. Pressured up to 1400#. Held OK.
- 6-23-68 - Circulated sand out to TD 2708. Swabbed well down, let set over-night. Found 750' of fluid in hole - mostly oil.
- 6-24-68 - Re-perforated - 20-~~3~~<sup>3</sup>/<sub>4</sub>" Lane-Wells bullets the following intervals: 2619' (1 shot), 2620' (1 shot), 2507-2524' (18 shots). Prep to Frac.
- 6-27-68 - Sand Fractured with 40,000# 20-40 sand, 40 gallons of 14N Surfactant and 1572 barrels of brine water. Treating rate 48 BPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE Agent DATE 6-27-68

APPROVED BY W. A. Gressett TITLE Oil and Gas Engineer DATE JUN 28 1968

CONDITIONS OF APPROVAL, IF ANY: