

FILE	7-
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

CORRECTED REPORT

MAY 6 1968

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Wilkinson "AZ"
3. Address of Operator 207 So. 4th St. - Artesia, New Mexico 88210		9. Well No. 2
4. Location of Well UNIT LETTER M 990 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 18S RANGE 25E NMPM.		10. Field and Pool, or Wildcat Penasco draw S. A. Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3467' GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1050' with 11" bit. Trip out, ran 33 jts of 8-5/8" 28# J-55S casing. Set at 1043'. Cemented with 350 sacks of Incor with 40# Gilsonite, 100# Flocele 2% gel additives, plus 50 sacks of Incor with 2% CaCl. Plug down at 5:00 P.M. (4-28-68). Ran temperature survey at 1:00 A.M. (4-29-68). Top of cement inside casing 955'. Top of cement behind 8-5/8" casing 350' from surface. Ran 3/4" tubing to bridge at 25'. Spotted 100 sacks of Incor with 6% CaCl. Filled to surface with 8 1/2 yards of medium Redi-Mix.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Pam White</i></u>	TITLE <u>Engineer</u>	DATE <u>5-3-68</u>
APPROVED BY <u><i>B. L. L. L.</i></u>	TITLE <u>Oil and Gas Inspector</u>	DATE <u>MAY 7 1968</u>
CONDITIONS OF APPROVAL, IF ANY:		