

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
 MAY 6 1968
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Wilkinson "AZ"
3. Address of Operator 207 So. 4th St. - Artesia, New Mexico 88210		9. Well No. 2
4. Location of Well UNIT LETTER <u>M</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM.		10. Field and Pool or Wildcat Penasco Draw S. A. Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3467' GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1530'. Laid down drill pipe and collars. Ran Gamma Ray-Neutron logs. Ran 48 jts 5½" J-55 S 14# casing to 1527'. Ran centralizer at 1483' and at 1321'. Cemented with 180 sacks Incor with 2% gel. Plug down at 8:15 P.M. (5-2-68). After 12 hours ran temperature survey. Top of cement at 1520'. Top of cement behind 5½" casing at 460' from surface. WOC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul White TITLE Engineer DATE 5-3-68

APPROVED BY P. H. Lane TITLE OIL AND GAS INSPECTOR DATE 5-3-68

CONDITIONS OF APPROVAL, IF ANY: