

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator The Fundamental Oil Corporation		8. Farm or Lease Name Thorp-Sears Con.	
3. Address of Operator 516 Gulf Building, Midland, Texas 79701		9. Well No. 1	
4. Location of Well UNIT LETTER P , 990 FEET FROM THE South LINE AND 990 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 18N RANGE 26E NMPM.		10. Field and Pool, or Wildcat Atoka Penn. Uni.	
15. Elevation (Show whether DF, RT, GR, etc.) 3412 G. R.		12. County Midy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Re-Plugging Operation <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged in 1968. Later inspection found gas leak. 7-27-69, rigged unit, found cement plug from 666' to 754' no plug at shoe of 8 5/8". Found plug at 2095', drill cement to 2105'. Re-plug as follows:

25 ex. 2092' - 2027' (Glorietta)
50 ex. 1282' - 1152' (In and out of 8 5/8" csg.)
40 ex. 688' - 563' (Between Grayburg and San Andres)
10 ex. 25' - Surface

Install 4" x 4' marker and clear location.

Plugging complete 7-27-69.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>J. R. Butts</i></u>	TITLE <u>Agent</u>	DATE <u>7-29-69</u>
APPROVED BY <u><i>R. L. Lamm</i></u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>AUG 25 1969</u>
CONDITIONS OF APPROVAL, IF ANY:		