

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator FRANKLIN, ASTON & FAIR, INC.	8. Farm or Lease Name Smith
3. Address of Operator P. O. Box 1090, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 18S RANGE 26E N.M.P.M.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3415' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

J-55

On November 12, 1968, 7" 20# casing was set at 1210' using 350 sacks Class C cement with 4% gel and 1/4# Flo-Seal per sack plus 200 sacks Class H cement, 2% CaCl. Cement did not circulate. Ran temperature survey and found top of cement 400' from surface. Ran 1" pipe down hole outside casing and circulated with 135 sacks Class C cement with 100# Flo-Seal and 2% CaCl. Mr. Gressett of O.C.C. was present during cementing operations which were conducted by Halliburton. After waiting 24 hours, pressured up to 500 psi on casing and held for 15 minutes. Pressure held, cement job okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ernest M. Smith

TITLE Geologist

DATE 11/22/68

APPROVED BY W. A. Gressett

TITLE Regional Geologist

DATE 11/23/68

CONDITIONS OF APPROVAL, IF ANY: