

**RECEIVED**

**JUN 4 1969**

**NEW MEXICO OIL CONSERVATION COMMISSION  
O.C.C.  
ARTESIA, OFFICE**

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name W. Loco Hills G. 4S. UT
8. Farm or Lease Name Tract 43
9. Well No. 3
10. Field and Pool, or Wildcat Loco Hills
12. County Eddy

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>WIW</b>
2. Name of Operator <b>NEWMONT OIL COMPANY</b>
3. Address of Operator <b>P. O. BOX 1305, ARTESIA, NEW MEXICO 88210</b>
4. Location of Well UNIT LETTER <b>L</b> , <b>1960</b> FEET FROM THE <b>South</b> LINE AND <b>1310</b> FEET FROM THE <b>East</b> LINE, SECTION <b>4</b> TOWNSHIP <b>18S</b> RANGE <b>29E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>3522 Gr.</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <b>Completion Report</b> <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well drilled and completed as follows:

- 3-3-69 Drilled to 390' and set 390' of 8 5/8" OD 20# new casing with 50 sks cement
- 3-8-69 Drilled to 2582' and log well
- 3-12-69 Rig up and cut side wall cores from 2546-43, 43-30, 40-37, 37-34 & 30-27.
- 3-15-69 Ran 2581' of 4 1/2" OD 9.5# new casing and cemented with 150 sks.
- 3-17-69 Perforate from 2534-43 with 4 each NCF 11 charges per foot.
- 3-19-69 Treat well with 1900 gals 15% reg. acid and shut well in.
- 4-20-69 Hook up and started water injection

Injection first five days averaged 500 BPD at 725 psi

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Herman J. Sedlitz* TITLE Division Superintendent DATE May 27, 1969

APPROVED BY *R. L. Starnes* TITLE OIL AND GAS INSPECTOR DATE JUN 9 1969

CONDITIONS OF APPROVAL, IF ANY: