

~~ROSWELL DISTRICT COPY~~

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED BY LEASE  
NOV 28 1983

LC 058579

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ - Water Injection Well

2. NAME OF OPERATOR

Anadarko Production Company ✓

3. ADDRESS OF OPERATOR

P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2460' FNL & 180' FEL, Sec 4, T18S, R29E

AT TOP PROD. INTERVAL: Same Eddy County, N.M.

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rigged up pulling unit.
2. Circulated hole with mud consisting of 10# brine with salt gel.
3. 1st. Plug: 2560' - 1960' (50 sx); tagged plug @ 2105'.
4. Perforated 4 cement squeeze holes @ 930' (100' below salt section).
5. 2nd. Plug: 937' - 582' (30 sx); squeezed 18 sx out squeeze holes @ 0 psig; tagged plug @ 795'.
6. Perforated 4 cement squeeze holes @ 385' (5' above 8-5/8" casing shoe & 10' above top of salt section).
7. 3rd. Plug: 385' - 0' (132 sx). Circulated cement down 4 1/2" casing and up 8-5/8" casing annulus to surface.
8. Erected P & A marker, cleaned & leveled location and cut off tiedowns.

Note: Mud consisting of 10# brine with salt gel was used between all plugs.  
Cement was Class H.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim E. Huels TITLE Area Supervisor DATE May 28, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

Post FD-2  
12-2-83  
P+A