

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other Instru. on re-
verse side)

LICATE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028990 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Creek "AL"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 24-18S-30E
NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

N.Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

SW SE 330' FSL & 1980' FEL of Sec. 24-18S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3617' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set 5 1/2" csg. & Perforate

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-11-69 - TD 3485'. Ran 3476' of 5 1/2" 15# J-55 casing with 1 float shoe set at 3476' and cemented with 150 sacks of Neat 2% CaCl. Plug down at 4:00 PM 10-11-69.

10-17-69 - TD 3485'. Perforated from 3384-3374 with 12 holes, 3366-3358' with 8 holes, using Dressler Atlas .38" Jet E Gun Bullets, then Sand Frac'd with 30000 gal brine water, 30000# 20-40 sand and 1500 gal of 15% acid. Injection rate 34.4 BPM, Max. Pressure 2500#, avg. 2200#, pump pressure 1750#. SI pressure - immediate 1500#, 10 min. 1150#.

RECEIVED

OCT 24 1969

O. C. C.
ARTESIA, OFFICE

OCT 23 1969

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard C. Morrison

TITLE

Geologist

DATE

10-23-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES

OCT 23 1969

Date

ACTING District Engineer

*See Instructions on Reverse Side