

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instruct.
verse side)CATE*
on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028990 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Yates Petroleum Corporation		8. FARM OR LEASE NAME Creek "AL"	
3. ADDRESS OF OPERATOR 207 So. 4th Street - Artesia, New Mexico		9. WELL NO. 5	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface SE SW 330' FSL & 2310' FWL of Sec. 24-18S-30E		10. FIELD AND POOL, OR WILDCAT Shugart	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 24-18S-30E NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3564' GR		12. COUNTY OR PARISH Eddy	
		13. STATE N.Mex.	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

Spud

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-20-69 - Spudded 11:00 AM 10-20-69.

10-29-69 - TD 782'. Drilled 10" hole to 782'. Ran 782' of 8 5/8" 24# used casing and 1 Regular Pattern Shoe and set at 782'. Cemented with 100 sx of Regular cement, 8 sacks salt and 2 sacks of 2% CaCl. Plug down 12 noon 10-29-69. WOC 36 hrs. Bailed hole dry. Tested for 1 hr. - Hole tested dry. Drilled plug. Reduced hole to 8" and resumed drilling.

RECEIVED
NOV-3-1969
U. S. GEOLOGICAL SURVEY
ARTESIA, N.M.

RECEIVED
NOV 5 1969
O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard C. Norman

TITLE

Geologist

DATE

11-3-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES

NOV - 4 1969

Date

ACTING

District Engineer

*See Instructions on Reverse Side