

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>David Fackler</i>		Lease <i>Brown Yates Com</i>		Well # <i>1</i>	
Location of Well	Unit <i>16505 9900</i>	Section <i>I 24</i>	Township <i>18</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Worton Drilling Co</i>		Type of Equipment <i>Rotary</i>			
APPROVED CASING PROGRAM <i>12-14-70</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8"</i>	<i>48</i>		<i>500</i>	<i>500 Cmc.</i>
<i>12 1/4</i>	<i>8 5/8"</i>	<i>24</i>		<i>1300</i>	<i>600 "</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>Various</i>		<i>9000</i>	<i>450</i>
Casing Data: <i>13 3/8 520 - 3in.</i>					
Surface joints of <i>8 5/8</i> inch <i>24</i> # Grade <i>J-E ST+C API</i>					
(Approved) (Rejected)					
Inspected by <i>Prescott</i>			date <i>12-21-70</i>		
Cementing Program					
Size of hole <i>12 1/4 - 1250</i>		Size of Casing <i>8 5/8</i>		Sacks cement required	
Type of Shoe used <i>Knife</i>		Float collar used <i>1st 4 ft</i>		Btm 3 jts welded	
TD of hole <i>1250</i> Set <i>1229</i> Feet of <i>8 5/8</i> inch <i>24</i> # Grade <i>J-E API</i>					
New used csg. @ with <i>150</i> sacks neat cement around shoe class <i>C 27.00</i>					
+ <i>400</i> sack <i>additives</i> <i>1/2 block 27.00</i>					
Plug down @ <i>1</i> (AM) (PM) Date <i>12-21-70</i>					
Cement circulated <i>750</i>		No. of Sacks			
Cemented by <i>David Fackler</i>		Witnessed by			
Temp. Survey ran @		(AM) (PM) Date		top cement @	
Casing test @		(AM) (PM) Date			
Method Used		Witnessed by			
Checked for shut off @		(AM) (PM) Date			
Method used		Witnessed by			
Remarks: <i>LC @ 675 (Wah. well on loc. 204) Cont. 1230, 1162. 762, 840</i>					
<i>754, 522 1045, 840 + 522 (222) 10 1162, 762, 840</i>					