

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 7 LIFICATE*
(Other instrum. as on re-
verse side)Form approved.
Budget Bureau No. 42-R1442.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0334702

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Allied Federal

9. WELL NO.

2 (two)

10. FIELD AND POOL, OR WILDCAT

Undesignated (Grayburg)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 6, T-12-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

The Eastland Oil Company

3. ADDRESS OF OPERATOR

704 Western United Life Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660 feet from North line and 1,980 feet from East line.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,633' GR - 3,643' RDB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Casing setting ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11 inch hole at 7:30 P.M., December 31, 1970, and drilled to 681 feet in anhydrite. Ran 17 joints 20#, 8-5/8" casing, 666.41 feet, set at 679 feet. Cemented with 350 sacks Class A, 2 per cent CaCl₂. Cement in place at 11:00 P.M., January 1, 1971. Circulated out 10 sacks excess cement. Allowed cement to set 12 hours. Nipped up and tested casing with 800 psi for 30 minutes with no pressure leak-off. Drilled cement plug at 3 P.M., January 2, 1971.

RECEIVED

JAN 13 1971

O. C. C.
ARTESIA, OFFICE

RECEIVED

JAN 11 1971

U. S. GEOLOGICAL SURVEY
ARTESIA, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. J. Neal

TITLE Vice - President

DATE January 7, 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES

JAN 12 1971

Date

ACTING

District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.